



## WRA-M46-1

Monoblock Cooler Unit

### Product Features

- Monoblock cooling unit
- Suitable for panels up to 200 mm thick
- Serial connection possible
- Digital controller and temperature display
- Ventilated cooling

Monoblock cooling unit for temperature -5°C to +15°C

The WRA monoblock cooling unit delivers exceptional refrigeration performance for cold rooms. The monoblock is designed for saddle mounting and installation requires cutting holes in the cold room panels. The monoblock is suitable for all panels with a depth of up to 200 mm.

You can see the capacity of the monoblock in the drawings. The performance depends on different factors such as ambient temperature and setpoint temperature.

If you have a larger cold room, it is possible to connect several monoblocks and have them operate together. You choose one unit to be the master and control the temperature for all units on just one controller.

The monoblock is for indoor use only.

### Measures and Content

Temperature Range	°C	-5 to +15
Gross / Net Weight	kg	112 / 92

### Design and Material

Exterior Finish	White RAL9003
Interior Finish	-

### Cooling and Functions

Type of Defrost	Automatic, hot gas	
Refrigerant	R290	
Refrigerant Charge	g	2x150

### Power and Consumption

Annual Energy Cons.	kWh/year	12483
Energy Consumption	kWh/24h	34.2
Input Power	W	1900
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	40.1

### Dimensions

External Dimension (WxDxH)	mm	711 x 1254 x 828
Packed Dimension (WxDxH)	mm	840 x 1370 x 980 mm
40ft Container Load	pcs	32



Monoblock rear – no panel attached



Digital controller