



UPD200

Refrigerated Display Case

Product Features

- Double glazed glass on four sides
- Adjustable wire shelves
- Glass door
- Aluminium finish
- Strong wheels for mobility
- Ventilated cooling
- Internal LED light

Vertical refrigerated glass display

The UPD200 refrigerated display case has a contemporary design with an aluminium finish and double glazed glass on all four sides. It is an excellent choice for displaying for example cakes and desserts in cafes, restaurants, or canteens. It is easy to organize the content, as the wire shelves are adjustable. The ventilated cooling system is controlled by a digital temperature display. The cabinet has strong castors for mobility, two of them with brakes.

Measures and Content

Total Display Area	m ²	2.29
Temperature Range	°C	+2 to +12
Climate Class		4
Gross / Net Weight	kg	160 / 140
Gross / Net Volume	l	468 / 425

Design and Material

Door No & Type		1 hinged glass door
Tempered glass		Yes
Max load on Shelves	kg/m ²	72.48
Shelf Color		Stainless steel
Shelf Dimensions		511*486
Shelves No & Type		5 wire shelves
Castors		4 wheels, 2 with brake
Exterior Finish		Aluminium / SS304
Interior Finish		Aluminium / SS304
Interior Light		LED

Cooling and Functions

Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic
Refrigerant		R290
Refrigerant Charge	g	130
Thermometer		Yes

Power and Consumption

Energy Class		B
Energy Consumption	kWh/24h	4.99
Annual Energy Cons.	kWh/year	1822
EEl	%	18.5
Input Power	W	255
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	46

Dimensions

Internal Dimension (WxDxH)	mm	638 x 638 x 1180
External Dimension (WxDxH)	mm	706 x 706 x 1800
Packed Dimension (WxDxH)	mm	760 x 820 x 1930 mm
40ft Container Load	pcs	45



Adjustable shelves



Castors with and without brake