



FSC1200H

2-door display cooler with canopy

Product Features

- Illuminated canopy
- Internal vertical light
- Adjustable shelves
- Adjustable feet
- Ventilated cooling
- Hinged alu-framed glass door

2-door display cooler with canopy

The FSC range is with a light canopy. The possibility for customized branding is eye-catching and stimulate impulse sales. The unit keeps beverages cold whilst presenting and promoting the products to their best advantage.

This model is a popular choice for shops, convenience stores and supermarkets. It is standard with white exterior and interior. It comes with 5 adjustable white wire shelves, 2 self-closing hinged glass doors, 2 vertical full length LED lights inside the door frame and a LED light canopy.

Measures and Content

Temperature Range	°C	+2 to +10
Climate Class		4
Net Volume	l	645
Gross Volume	l	1082
Gross / Net Volume	l	1082 / 645
Gross / Net Weight	kg	189 / 174

Design and Material

No. of Doors		2
Door No & Type		2 hinged glass doors
No. of Shelves	pcs	5
Shelves No & Type		5 wire shelves white
Shelf Dimensions		1072 x 540 mm
Max load on Shelves	kg/m ²	196
Shelf Color		White
Bottom Shelf Dimensions		1070 x 475
Tempered glass		Yes
Canopy Light		LED
Canopy Type		D-Shape
Feet / Legs		4 adjustable feet
Castors		4 rollers
Interior Light		LED
Lock		Yes
Exterior Finish		White RAL9016
Interior Finish		White painted steel

Cooling and Functions

Compressor Type		AS APPROVED IN CE-APPROVAL
Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic
Refrigerant		R290
Refrigerant Charge	g	120
Thermometer		Yes

Power and Consumption

Energy Class		F
Max Ambient		+30°C, 55% RH
Annual Energy Cons.	kWh/year	2482
Energy Consumption	kWh/24h	6.8
EEL	%	72
Power Supply		13 Amp
Input Power	W	880
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	48

Dimensions

External Dimension (WxDxH)	mm	1200 x 790 x 2000
Internal Dimension (WxDxH)	mm	1090 x 670 x 1533
Packed Dimension (WxDxH)	mm	1250 x 840 x 2100
40ft Container Load	pcs	23



Strong handles



Vertical internal light