



BLCA3X1

Blast Chiller/Freezer GN1/1

Product Features

- Core sensor included
- Guides for GN1/1 and Euronorm pans
- Programmable thermostat
- Reversible self-closing door
- Stainless steel
- Adjustable legs
- Touch screen controller
- HACCP compliant data export

Blast chiller/freezer with touch screen controller

Our blast chiller/freezer range is perfect for quickly cooling or freezing hot food from the stove or oven, preserving the food in a safe way. The BLCA-X comes with an easy-to-use touch screen controller. Here you can choose one of the pre-set programs for different purposes or you can create and save your own programs. The unit comes with pre-set special cycles for fish, hardening of ice cream, drying as well as for defrosting. It is possible to upload your own recipes or download data for HACCP purposes via an USB port.

Primary programs are pre-set to keep the end temperature fixed until the cabinet is opened and the program is turned off. This method ensures the quality and safe preservation of the food and makes sure the food is safe for storage and later consumption.

Cooling capacity is measured from +70 to +3 °C in 90 minutes - Freezing capacity is measured from +70 to -18 °C in 240 minutes. Exact kg capacity for each model can be found under the technical specifications.

The BLCA-X accepts both gastronorm 1/1 and euronorm pans (not included).

Measures and Content

Gross / Net Weight	kg	130 / 104
Net Volume	l	60
Gross Volume	l	139
Gross / Net Volume	l	139 / 60
Capacity GN Pans	pcs	3 x GN1/1
Capacity Cooling	kg	12
Capacity Freezing	kg	8
Temperature Range	°C	-30 to +70

Design and Material

Exterior Finish	SS304
Interior Finish	SS304
Door No & Type	1 hinged self-closing solid door
Door Reversible	Yes
Feet / Legs	4 adjustable feet

Cooling and Functions

Type of Controller	Programmable Touchscreen	
Type of Defrost	Automatic, hot gas	
Refrigerant	R290	
Refrigerant Charge	g	130

Power and Consumption


Input Power	W	700
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	60

Dimensions

External Dimension (WxDxH)	mm	804 x 826 x 995
Internal Dimension (WxDxH)	mm	660 x 640 x 330
Packed Dimension (WxDxH)	mm	870 x 900 x 1030
40ft Container Load	pcs	52



Core sensor included



Touch screen controller