



CRPF1230

Cold Room

Product Features

- Plug-In - ready after assembly
- Many customisation possibilities
- Easy access to products
- Easy assembly
- Anti-slip floor in SS304 stainless steel
- 80 mm panel insulation
- Shelves available as accessory
- Ramp available as accessory for easy access

Easy, economic and effective storage in cold rooms

Measures and Content

| | | |
|--------------------|-------------------|-----------|
| Insulation Density | kg/m ³ | 42 |
| Wall Thickness | mm | 80 |
| Internal Volume | m ³ | 6.03 |
| Temperature Range | °C | 0 to +8 |
| Climate Class | | 5 |
| Gross / Net Weight | kg | 325 / 295 |
| Gross / Net Volume | l | |

Design and Material

| | | |
|-------------------|----------------------------------|------|
| Door No & Type | 1 hinged solid door W:580 H:1845 | |
| Max Load on Floor | kg/m ² | 1500 |
| Exterior Finish | White | |
| Interior Finish | White | |
| Interior Light | LED | |
| Lock | Yes | |

Cooling and Functions

| | | |
|--------------------|--------------------|-----|
| Type of Controller | Electronic | |
| Type of Cooling | Ventilated | |
| Type of Defrost | Automatic, hot gas | |
| Refrigerant | R290 | |
| Refrigerant Charge | g | 130 |
| Thermometer | Yes | |

Power and Consumption

| | | |
|---------------------|----------|------------|
| Energy Consumption | kWh/24h | 18.72 |
| Annual Energy Cons. | kWh/year | 6833 |
| Input Power | W | 860 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Noise Level | dB(A) | 60 |

Dimensions

| | | |
|----------------------------|-----|-----------------------|
| Internal Dimension (WxDxH) | mm | 1040 x 2840 x 2040 |
| External Dimension (WxDxH) | mm | 1200 x 3000 x 2200 |
| Packed Dimension (WxDxH) | mm | 3100 x 1300 x 2400 mm |
| 40ft Container Load | pcs | 3 |



Strong handle



Shelf as accessory

Cold rooms are perfect as plug-in with quick and easy assemble.

The cooling unit comes completely pre-mounted in a panel and does not require extra expert knowledge. The interchangeable modular panels even allow varies positioning of both the panel with the cooling unit and the panel with the door.

The cold room can be used in both restaurants, delis, cafes etc. They are a great way to create optimal and efficient cooling space at a very affordable price. Cold rooms are a perfect and easy accessible way to store foods, dairy products and beverages.

The many different cold room sizes give a good fit in most conditions. Cold rooms are available as both cooler and freezer models. Shelves are optional. A ramp is also available as an option to provide easy access with lightweight trolleys and bakery racks (the cold room is not suitable for pallet jacks/pallet trucks).

Our range of cold rooms have a low energy consumption due to the effective polyurethane insulation in the panels combined with an energy efficient cooling system.

Not suitable for outdoor use.