

## EIB-D1020-B1

Black impulse cooler/freezer

### Product Features

- Easily switchable between cooler and freezer
- Temperature Class 3M1/3L1
- Glass sides for better presentation of products
- Ventilated cooling
- LED interior light
- Sliding glass lids
- Controller with Bluetooth and NFC connectivity
- HACCP compliant data export
- Stainless steel bumper bars on all four sides
- Ticket strip included
- Castors, 2 lockable

Versatile impulse cooler/freezer

The EIB mobile cooler/freezer from TEFCOLD offers a flexible solution for retail spaces. With its versatile cooling and freezing capabilities, ample storage space, and eye-catching design, this unit is ideal for driving impulse purchases. Switch effortlessly between cooling and freezing modes to suit your needs. It is temperature class 3M1/3L1, ideal for retail settings. The EIB has a digital controller with Bluetooth for convenient HACCP data monitoring and export. Simply download the app on your phone and connect it to the unit. The interior LED lighting combined with four glass sides and sliding lids offer excellent product visibility, inviting customers to indulge. Castors with brakes ensure mobility, allowing you to strategically place the unit for maximum impact. Available in several sizes, this impulse merchandiser is the perfect addition to any retail setting.

### Measures and Content

Gross / Net Weight	kg	415 / 380
Gross / Net Volume	l	640 / 427
Total Display Area	m <sup>2</sup>	2.93
Temperature Range	°C	-18 to +5
Climate Class		3

### Design and Material

Exterior Finish	Black RAL9005
Interior Finish	Black RAL9005
Number of lids	2
Lid No & Type	2 flat sliding glass lid
Tempered glass	Yes
Castors	Wheels
Interior Light	LED Horizontal

### Cooling and Functions


Type of Controller	Electronic	
Type of Cooling	Ventilated	
Type of Defrost	Automatic, hot gas	
Refrigerant	R290	
Refrigerant Charge	g	149
Thermometer	Yes	

### Power and Consumption

Energy Class	C	
Max Ambient	+25°C, 60% RH	
Energy Consumption	kWh/24h	12.14
Annual Energy Cons.	kWh/year	4431.1
EEL	%	32.29
Input Power	W	1649
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	54

### Dimensions

External Dimension (WxDxH)	mm	2012 x 1010 x 975
Internal Dimension (WxDxH)	mm	1860 x 790 x 300
Packed Dimension (WxDxH)	mm	2070 x 1070 x 1155
40ft Container Load	pcs	22



Strong handle



Digital controller