



450

## LGC2500B

### Display Cooler

#### Product Features

- LED illuminated canopy
- Self closing doors with stay open feature for easy loading
- Temperature Class 3M1
- Adjustable shelves
- LED interior light with switch
- Digital controller and temperature display
- Internal stainless steel base
- Ventilated cooling
- Automatic defrost
- Castors and locking feet

### Elegant black display cooler with canopy

The LGC-B display cooler is designed to integrate effortlessly into your retail or catering setting, adding a touch of elegance and quality with its stylish black finish. It features two vertical LED light strips on each door, which highlight the contents inside with an eye-catching contrast against the dark interior. Moreover, an LED illuminated canopy tops the unit, providing an outstanding opportunity for customized branding and promotional displays.

The unit's interior base is manufactured from stainless steel and features curved corners to help with cleaning and hygiene. The carefully engineered refrigeration system is highly energy-efficient, reducing costs while maintaining the ideal temperature for product freshness. For added convenience, the unit includes castors, making it easy to move for cleaning and repositioning as needed.

#### Measures and Content

Gross / Net Weight	kg	135 / 115
Net Volume	l	405
Gross Volume	l	496
Gross / Net Volume	l	496 / 405
Total Display Area	m <sup>2</sup>	0.69
Temperature Range	°C	+1 to +8
Climate Class		4

#### Design and Material

Exterior Finish		Black RAL9005
Interior Finish		Black
No. of Doors		1
Door No & Type		1 hinged glass door
No. of Shelves	pcs	5
Shelves No & Type		5
Shelf Dimensions		545*622
Max load on Shelves	kg/m <sup>2</sup>	196
Tempered glass		Yes
Lock		Yes
Interior Light		LED

#### Cooling and Functions

Type of Defrost		Automatic / Off Cycle
Refrigerant		R600a
Refrigerant Charge	g	110
Thermometer		Yes

#### Power and Consumption

Energy Class		B
Max Ambient		+30°C, 55% RH
Energy Consumption	kWh/24h	3.7
Annual Energy Cons.	kWh/year	1349
EEL	%	19
Input Power	W	280
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	58

#### Dimensions

External Dimension (WxDxH)	mm	685 x 805 x 2065
Internal Dimension (WxDxH)	mm	565 x 640 x 1520
Packed Dimension (WxDxH)	mm	745 x 860 x 2260
40ft Container Load	pcs	44



Illuminated canopy



Strong castors