



BERMUDA RV10

Ventilated Scoop Ice Cream Display

Product Features

- Perfect temperature distribution
- Heated glass to help prevent condensation
- Suitable for Napoli Pans (not included)
- LED interior light with switch
- Digital controller and temperature display
- Easy access storage compartment
- Rear night curtain to maintain temperature
- Ventilated cooling
- Automatic defrost

Ventilated scoop ice cream display with understorage

The Bermuda RV10 ice cream scooping cabinet accommodates 10 Napoli pans. Its ventilated cooling system ensures that your gelato or ice cream is maintained at the perfect serving temperature. In addition, the cabinet is equipped with a separate refrigerated under storage, which enables fast restocking of the display without leaving the unit. The Bermuda model has a sleek curved glass feature that is both practical and elegant and the front glass is heated to help prevent condensation. This unit is equipped with castors for easy mobility and an internal LED light that beautifully illuminates your products. With its exceptional blend of quality and affordability, the Bermuda range has become a popular choice among ice cream and gelato vendors.

Measures and Content

Total Display Area	m ²	0.59
Serving Capacity		10 Napoli pans (5 L)
Serving Capacity		/ 10 Napoli Pans (5L)
Storage Capacity (under)		10 Napoli pans (5 L)
Storage Capacity (under)		/ 10 Napoli Pans (5L)
Temperature Range	°C	-20 to -14
Climate Class		4
Gross / Net Weight	kg	200 / 180

Design and Material

Tempered glass		Yes
Castors		4 castors
Interior Light		LED
Lock		No
Exterior Finish		Grey
Interior Finish		White painted steel

Cooling and Functions


Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic, hot gas
Refrigerant		R290
Refrigerant Charge	g	130
Thermometer		Yes

Power and Consumption

Energy Class		E
Max Ambient		+30°C, 55% RH
Annual Energy Cons.	kWh/year	8103
Energy Consumption	kWh/24h	22.2
EEl	%	51.6
Power Supply		13 Amp
Input Power	W	770
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	54

Dimensions

External Dimension (WxDxH)	mm	1340 x 800 x 1343
Packed Dimension (WxDxH)	mm	1410 x 860 x 1466
40ft Container Load	pcs	16



Strong castors



Easy access storage compartment