



IC202SCE-SO

Scoop Ice Cream Freezer

Product Features

- Sneeze guard in curved glass
- Angled sliding lids with lock
- Storage under baskets
- LED interior light
- Castors with brake
- Climate class 5 for high performance in warm surroundings
- Optional - Scooping baskets

Scoop ice cream freezer - angled and with serveover

The IC-SO range is our price friendly basis chest freezer with a serve over glass top. It is a quality scoop ice cream freezer for a fair price. It is perfect if you wish to add scooping ice cream sales to your business and are on a budget.

This model is with flat sliding glass lids with a lock.

The model is still compact and comes in varies sizes, so that it is perfect for both smaller shops and delis with limited space as well as lager shops, gas stations and supermarkets. It is on wheels and can easily change location in the shop. It is ideal for branding for better presentation of the cabinet content.

Baskets are optional. Type and number must be ordered under accessories.

Ideal baskets for scoop ice

- For 5L plastic tubs: 1x item no. 14708 (4 x 5L)
- For 5L Napoli pans: 1x item no. 14704 (3 x 5L)
- For 4L plastic tubs: 3x 21285 (6 x 4L)

Measures and Content

Serving Capacity	4 Plastic Tubs (5 L)
Serving Capacity	4 Plastic Tubs (5L) / 3 Napoli Pans (5L) / 6 Plastic Tubs (4L)
Storage Capacity (under)	7 Plastic Tubs (5 L)
Storage Capacity (under)	7 Plastic Tubs (5L) / 7 Napoli Pans (5L) / 7 Plastic Tubs (4L)

Temperature Range	°C	-24 to -14
Climate Class		5
Net Volume	l	144
Gross Volume	l	176
Gross / Net Volume	l	176 / 144
Gross / Net Weight	kg	96 / 89

Design and Material

Tempered glass	Yes
Castors	4 wheels, 2 with brake
Interior Light	LED
Lock	Yes
Exterior Finish	White
Interior Finish	White painted steel

Cooling and Functions

Type of Controller	Mechanical
Type of Cooling	Static
Type of Defrost	Manual
Refrigerant	R600a
Refrigerant Charge	g55
Thermometer	Yes

Power and Consumption

Energy Class		D
Annual Energy Cons.	kWh/year	561
Energy Consumption	kWh/24h	1.537
Input Power	W	200
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	45

Dimensions

Internal Dimension (WxDxH)	mm	500 x 495 x 710
External Dimension (WxDxH)	mm	720 x 615 x 1295
Packed Dimension (WxDxH)	mm	800 x 750 x 1200
40ft Container Load	pcs	92



Scooping basket option



Scoop wash option