TEFCOLD®
COOL PRODUCTS WORLDWIDE

1000

LGC5000B

Display Cooler

Product Features
- LED illuminated canopy
- Self closing doors with stay open feature for easy loading
- Temperature Class 3M1
- Adjustable shelves
- LED interior light with switch
- Digital controller and temperature display
- Internal stainless steel base
- Ventilated cooling
- Automatic defrost
- Castors and locking feet

Elegant black display cooler with canopy

The LGC-B display cooler is designed to integrate effortlessly into your retail or catering setting, adding a touch of elegance and quality with its stylish black finish. It features two vertical LED light strips on each door, which highlight the contents inside with an eye-catching contrast against the dark interior. Moreover, an LED illuminated canopy tops the unit, providing an outstanding opportunity for customized branding and promotional displays.

The unit's interior base is manufactured from stainless steel and features curved corners to help with cleaning and hygiene. The carefully engineered refrigeration system is highly energy-efficient, reducing costs while maintaining the ideal temperature for product freshness. For added convenience, the unit includes castors, making it easy to move for cleaning and repositioning as needed.

Measures and Content		
Gross / Net Weight	kg	210 / 190
Net Volume	l	922
Gross Volume	l	1108
Gross / Net Volume	l	1108 / 922
Total Display Area	m²	1.38
Temperature Range	°C	+1 to +8
Climate Class		4
Design and Material		
Exterior Finish		Black RAL9005
Interior Finish		Black
No. of Doors		2
Door No & Type		2 hinged glass doors
No. of Shelves	pcs	10
Shelves No & Type		10
Shelf Dimensions		618*622
Max load on Shelves	kg/m²	196
Tempered glass		Yes
Lock		Yes
Interior Light		LED
Cooling and Functions		
Type of Defrost		Automatic / Off Cycle
Refrigerant		R290
Refrigerant Charge	g	120
Thermometer		Yes
Power and Consumption		
Energy Class		B
Max Ambient		+30°C, 55% RH
Energy Consumption	kWh/24h	5.21
Annual Energy Cons.	kWh/year	1900
EEI	%	19
Input Power	W	400
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	58
Dimensions		
External Dimension (WxDxH)	mm	1382 x 805 x 2065
Internal Dimension (WxDxH)	mm	1262 x 640 x 1520
Packed Dimension (WxDxH)	mm	1430 x 860 x 2260
40ft Container Load	pcs	22

Illuminated canopy

Strong castors