



BA26S

Backbar Cooler

Product Features

- EU Energy Class A
- App. 59% more energy efficient than previous BA-range
- Double glazed tempered glass
- Energy saving variable speed compressor
- Self-closing sliding glass doors
- Ventilated cooling for fast pull-down and even temperature
- Easy access electronic thermostat
- Adjustable shelves behind each door
- LED interior light
- Lock

High-quality backbar with low energy consumption

The BA is our range of high-quality backbars. It has been updated and now uses in average 59% less energy compared to the previous models from the same range. This backbar has ventilated cooling for a short pull-down time to ensure that you can keep up with customer demand for cold beverages. If you need to adjust the temperature this is easily done on the electronic thermostat.

The backbar cooler is made of solid materials and has adjustable chrome shelves with closely-spaced wires, which gives you a high capacity and stability. Furthermore, it has self-closing aluminium sliding doors with double glazed tempered glass. This helps save energy, but it also means a great product visibility.

The BA range is also available in a variant with hinged doors.

Measures and Content

Total Display Area	m ²	0.52
Temperature Range	°C	+2 to +10
Climate Class		4
Net Volume	l	182
Gross Volume	l	190
Gross / Net Volume	l	190 / 182
Gross / Net Weight	kg	69 / 63

Design and Material

No. of Doors		2
Door No & Type		2 sliding glass doors
No. of Shelves	pcs	4
Shelves No & Type		4 wire shelves chrome
Shelf Color		Chrome
Shelf Dimensions		395x328 mm
Tempered glass		Yes
Feet / Legs		4 adjustable feet
Interior Light		LED
Lock		Yes
Exterior Finish		Black
Interior Finish		Stucco aluminium

Cooling and Functions

Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic
Refrigerant Charge	g	70
Refrigerant		R600a
Thermometer		Yes

Power and Consumption

Energy Class		A
Max Ambient		+30°C, 55% RH
Annual Energy Cons.	kWh/year	416
Energy Consumption	kWh/24h	1.14
EEL	%	9
Power Supply		13 Amp
Input Power	W	115
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	44

Dimensions

External Dimension (WxDxH)	mm	900 x 515 x 870
Internal Dimension (WxDxH)	mm	810 x 418 x 720
Packed Dimension (WxDxH)	mm	985 x 575 x 940
40ft Container Load	pcs	96



Door holder for loading
of the cabinet

Electronic thermostat