



WRA-L11-1

Monoblock Freezers Unit

Product Features

- Monoblock freezing unit
- Suitable for panels up to 200 mm thick
- Serial connection possible
- Digital controller and temperature display
- Ventilated cooling

Monoblock freezing unit for temperature -25°C to -10°C

The WRA monoblock freezing unit delivers exceptional refrigeration performance for freezer rooms. The monoblock is designed for saddle mounting and installation requires cutting holes in the freezer room panels. The monoblock is suitable for all panels with a depth of up to 200 mm.

You can see the capacity of the monoblock in the drawings. The performance depends on different factors such as ambient temperature and setpoint temperature.

If you have a larger freezer room, it is possible to connect several monoblocks and have them operate together. You choose one unit to be the master and control the temperature for all units on just one controller.

The monoblock is for indoor use only.

Measures and Content		
Temperature Range	°C	-25 to -10
Gross / Net Weight	kg	66 / 54
Design and Material		
Exterior Finish		White RAL9003
Interior Finish		-
Cooling and Functions		
Type of Defrost		Automatic, hot gas
Refrigerant		R290
Refrigerant Charge	g	150
Power and Consumption		
Annual Energy Cons.	kWh/year	5979
Energy Consumption	kWh/24h	16.38
Input Power	W	910
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	42.5
Dimensions		
External Dimension (WxDxH)	mm	421 x 876 x 728
Packed Dimension (WxDxH)	mm	500 x 970 x 890 mm
40ft Container Load	pcs	52



Monoblock rear – no panel attached



Digital controller