



EXTRA1250FD

Supermarket Multideck Freezer

Product Features

- Can be multiplexed - Create uninterrupted continuous line
- Temperature Class 3L1
- Heated self-closing glass doors
- Adjustable extra deep shelves to maximise capacity
- Base plus 4 shelves
- Internal vertical LED light
- Solid end walls as standard
- Multiplexing kit as accessory

Full Class Door Multideck Freezer with Multiplexing Opti

EXTRA Multideck is a premium full glass door freezer with double glazed hinged glass doors for added energy efficiency savings on running costs. For greater stock capacity it has 460mm deep shelves to help maximise sales during busy periods and reduce restocking. It has excellent internal illumination with vertical LED lighting in each door and horizontally across the top on the 2500 model. Wire shelving with ticket strips and shelf risers are supplied as standard. Installation is simple and quick. No special requirements as refrigerant charge is below 150g. The model allows for multiplexing and increases your possibilities to make the most of the space, you have available. The unit can be ordered without end walls and with a multiplexing kit if required.

Measures and Content

Total Display Area	m ²	1.53
Temperature Range	°C	-21 to -18
Gross / Net Weight	kg	350 / 330
Gross Volume	l	880
Net Volume	l	850
Gross / Net Volume	l	880 / 850

Design and Material

Door No & Type	2 hinged glass doors	
Tempered glass	Yes	
No. of Doors	2	
Max load on Shelves	kg/m ²	150
No. of Shelves	pcs	8
Shelf Color	Black	
Shelves No & Type	8 wire shelves black	
Feet / Legs	4 adjustable feet	
Castors	Option	
Exterior Finish	Black / Glass	
Interior Finish	Black	
Interior Light	2 x Vertically LED	
Lock	No	

Cooling and Functions

Type of Controller	Electronic	
Type of Cooling	Ventilated	
Type of Defrost	Automatic, hot gas	
Refrigerant	R290	
Refrigerant Charge	g	149
Thermometer	Yes	

Power and Consumption

Energy Class	D	
Energy Consumption	kWh/24h	15.28
Annual Energy Cons.	kWh/year	5578
EEl	%	37.5
Input Power	W	1100
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	53

Dimensions

Internal Dimension (WxDxH)	mm	1250 x 610 x 1399
External Dimension (WxDxH)	mm	1350 x 930 x 2035
Packed Dimension (WxDxH)	mm	1450 x 975 x 2230 mm
40ft Container Load	pcs	16



Extraordinary space on shelves



Electronic thermostat