



IDA400-W1

Ice Cream Freezer

Product Features

- Sliding glass lids
- Internal LED light
- Ideal for branding
- Strong castors
- Static cooling
- Baskets are available as accessories (not included)
- Storage under baskets

Chest freezer for a great product display

The IDA ice cream freezer offers a great customer experience with sliding lids that open smoothly, thanks to small wheels on the back. The freezer has interior LED lighting at the front, illuminating your ice cream flavors beautifully. It's straightforward design makes it ideal for branding, while sturdy castors with brakes ensures mobility.

Be aware that the freezer does not include baskets. We offer different types of baskets, these can be ordered as accessories.

Ideal baskets for scoop ice:

2 x item no. 71975 (10 x 5L + 2 x 2,5L)

Measures and Content

| | | |
|--------------------|----|------------|
| Temperature Range | °C | -23 to -16 |
| Climate Class | | 7 |
| Net Volume | l | 345 |
| Gross Volume | l | 426 |
| Gross / Net Volume | l | 426 / 345 |
| Gross / Net Weight | kg | 65 / 61 |

Design and Material

| | | |
|--------------------|-----|---------------------------|
| Tempered glass | | Yes |
| Number of lids | | 2 |
| Lid No & Type | | 2 flat sliding glass lids |
| No. of baskets | pcs | 0 |
| Basket No & Type | | 0 Wire basket |
| Max No. of Baskets | pcs | 2 |
| Castors | | Wheels |
| Interior Light | | LED |
| Lock | | No |
| Exterior Finish | | White RAL9010 |
| Interior Finish | | White RAL9010 |

Cooling and Functions


| | | |
|--------------------|---|------------|
| Type of Controller | | Mechanical |
| Type of Cooling | | Static |
| Type of Defrost | | Manual |
| Refrigerant | | R290 |
| Refrigerant Charge | g | 80 |
| Thermometer | | Yes |

Power and Consumption

| | | |
|---------------------|----------|----------------|
| Energy Class | | C |
| Max Ambient | | 35°C at 75% RH |
| Annual Energy Cons. | kWh/year | 668.32 |
| Energy Consumption | kWh/24h | 1.831 |
| EEL | % | 33.8 |
| Input Power | W | 112 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Noise Level | dB(A) | 49 |

Dimensions

| | | |
|----------------------------|-----|------------------|
| External Dimension (WxDxH) | mm | 1344 x 694 x 867 |
| Internal Dimension (WxDxH) | mm | 1186 x 536 x 688 |
| Packed Dimension (WxDxH) | mm | 1390 x 760 x 920 |
| 40ft Container Load | pcs | 40 |



Strong handles



Thermometer