



BA31S-3

Backbar Cooler

Product Features

- EU Energy Class B
- Approx. 59% more energy efficient than previous BA-range
- Double glazed tempered glass
- Energy saving variable speed compressor
- Self-closing sliding glass doors
- Ventilated cooling for fast pull-down and even temperature
- Easy access electronic thermostat
- Adjustable shelves behind each door
- LED interior light
- Lock

High-quality backbar with low energy consumption

The BA is our range of high-quality backbars. It has been updated and now uses in average 59% less energy compared to the previous models from the same range. This backbar has ventilated cooling for a short pull-down time to ensure that you can keep up with customer demand for cold beverages. If you need to adjust the temperature this is easily done on the electronic thermostat.

The backbar cooler is made of solid materials and has adjustable chrome shelves with closely-spaced wires, which gives you a high capacity and stability. Furthermore, it has self-closing aluminium sliding doors with double glazed tempered glass. This helps save energy, but it also means a great product visibility.

The BA range is also available in a variant with hinged doors.

Measures and Content

| | | |
|--------------------|----------------|-----------|
| Total Display Area | m ² | 0.84 |
| Temperature Range | °C | +2 to +10 |
| Climate Class | | 4 |
| Net Volume | l | 288 |
| Gross Volume | l | 311 |
| Gross / Net Volume | l | 311 / 288 |
| Gross / Net Weight | kg | 101 / 94 |

Design and Material

| | | |
|-------------------|-----|-----------------------|
| No. of Doors | | 3 |
| Door No & Type | | 3 sliding glass doors |
| No. of Shelves | pcs | 6 |
| Shelves No & Type | | 6 wire shelves chrome |
| Shelf Color | | Chrome |
| Shelf Dimensions | | 400x318 / 432x318 mm |
| Tempered glass | | Yes |
| Feet / Legs | | 4 adjustable feet |
| Interior Light | | LED |
| Lock | | Yes |
| Exterior Finish | | Black |
| Interior Finish | | Stucco aluminium |

Cooling and Functions

| | | |
|--------------------|---|------------|
| Type of Controller | | Electronic |
| Type of Cooling | | Ventilated |
| Type of Defrost | | Automatic |
| Refrigerant Charge | g | 90 |
| Refrigerant | | R290 |
| Thermometer | | Yes |

Power and Consumption

| | | |
|---------------------|----------|---------------|
| Energy Class | | B |
| Max Ambient | | +30°C, 55% RH |
| Annual Energy Cons. | kWh/year | 635 |
| Energy Consumption | kWh/24h | 1.74 |
| EEL | % | 12 |
| Power Supply | | 13 Amp |
| Input Power | W | 125 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Noise Level | dB(A) | 44 |

Dimensions

| | | |
|----------------------------|-----|------------------|
| External Dimension (WxDxH) | mm | 1350 x 515 x 900 |
| Internal Dimension (WxDxH) | mm | 1265 x 418 x 734 |
| Packed Dimension (WxDxH) | mm | 1435 x 575 x 970 |
| 40ft Container Load | pcs | 64 |



Door holder for loading
of the cabinet

Electronic thermostat