



IDA600-W1+

Scoop Ice Cream Freezer

Product Features

- Sneeze guard in curved glass
- Sliding glass lids
- Storage under baskets
- Ideal for branding
- Internal LED light
- Strong castors
- Static cooling

Static scoop ice cream freezer

The IDA scoop ice cream freezer offers a spacious and efficient solution for displaying ice cream. Its straightforward design and mobility on castors make it a great addition to any ice cream parlor or retail store. You can transform the clean design with customized branding, making the unit stand out and attract attention to your variety of flavors. The freezer features a curved glass sneezeguard and internal LED lighting to ensure a great product presentation, while sliding lids help save energy when not serving.

The static scoop ice cream freezer is optimized for baskets suitable for 5 l plastic tubs with room for storage underneath. Be aware that they are suitable for 5 l plastic tubs – Napoli pans will not fit in there. The baskets are not included, but can be ordered as accessories.

Ideal baskets for scoop ice:

2 x item no. 71975 + 1 x 69966 (14 x 5L + 2 x 2,5L)

The IDA range was previously named ISOA - nothing has changed except for the naming.

Measures and Content

Total Display Area	m ²	1.72
Serving Capacity		14 Plastic Tubs (5 L)
Serving Capacity		14 Plastic Tubs (5L) + 2 Plastic Tubs (2.5L)
Storage Capacity (under)		36 Plastic Tubs (5L)
Storage Capacity (under)		36 Plastic Tubs (5L)
Temperature Range	°C	-23 to -16
Climate Class		7
Gross / Net Weight	kg	133 / 126

Design and Material

Tempered glass		Yes
Castors		Wheels
Interior Light		LED
Lock		No
Exterior Finish		White RAL9010
Interior Finish		White RAL9010

Cooling and Functions


Type of Controller		Mechanical
Type of Cooling		Static
Type of Defrost		Manual
Refrigerant		R290
Refrigerant Charge	g	112
Thermometer		Yes

Power and Consumption

Energy Class		D
Max Ambient		35°C at 75% RH
Annual Energy Cons.	kWh/year	990
Energy Consumption	kWh/24h	2.71
EEl	%	39.6
Input Power	W	241
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	49

Dimensions

External Dimension (WxDxH)	mm	1804 x 694 x 1330
Packed Dimension (WxDxH)	mm	1860 x 760 x 920
40ft Container Load	pcs	28



Scooping basket option



Curved glass for nice presentation