



## DB301S-3

### Backbar Cooler

#### Product Features

- App. 56% more energy efficient than previous DB-range
- Double glazed tempered glass
- Energy saving variable speed compressor
- Ventilated cooling for fast pull-down and even temperature
- Easy access electronic thermostat
- Adjustable shelves
- LED interior light

#### Energy-efficient backbar cooler

This new range of DB backbars is highly energy efficient and uses in average 56% less energy compared to the previous models from the same range. This backbar has ventilated cooling for a short pull-down time to ensure that you can keep up with customer demand for cold beverages. The temperature is easily adjusted on the electronic thermostat.

The backbar cooler has self-closing sliding doors with double glazed tempered glass, which gives a nice product presentation. The adjustable wire shelves have a white plastic coating for easy maintenance. The backbar is ideal for busy bar environments, and with its black exterior and stucco aluminium interior it has a contemporary look. A great choice for any bar.

The DB range is also available in a variant with hinged doors.

#### Measures and Content

Total Display Area	m <sup>2</sup>	0.72
Temperature Range	°C	+2 to +10
Climate Class		4
Net Volume	l	278
Gross Volume	l	300
Gross / Net Volume	l	300 / 278
Gross / Net Weight	kg	95 / 88

#### Design and Material

No. of Doors		3
Door No & Type		3 sliding glass doors
No. of Shelves	pcs	6
Shelves No & Type		6 wire shelves white
Max load on Shelves	kg/m <sup>2</sup>	196
Shelf Color		White
Shelf Dimensions		395x320 mm / 432x320mm
Tempered glass		Yes
Feet / Legs		4 adjustable feet
Interior Light		LED
Lock		Yes
Exterior Finish		Black RAL9005
Interior Finish		Stucco aluminium

#### Cooling and Functions

Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic
Refrigerant Charge	g	90
Refrigerant		R600a
Thermometer		Yes

#### Power and Consumption

Type of refrigeration		Supermarket cabinet
Display cabinet family		VC4
Energy Class		B
Max Ambient		+30°C, 55% RH
Annual Energy Cons.	kWh/year	635
Energy Consumption	kWh/24h	1.74
EEl	%	12
Power Supply		13 Amp
Input Power	W	125
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	44

#### Dimensions

External Dimension (WxDxH)	mm	1350 x 526 x 870
Internal Dimension (WxDxH)	mm	1265 x 418 x 720
Packed Dimension (WxDxH)	mm	1435 x 575 x 940
40ft Container Load	pcs	64



Protective thermostat  
cover



Door holder for loading of  
the cabinet