



NIC302SC-SO

Scoop Ice Cream Freezer

Product Features

- Sneeze guard in curved glass
- Flat sliding glass lids with lock
- Great branding possibilities
- LED interior light
- Castors with brake
- Digital thermometer
- Powder coated white steel inner liner
- Optional - Scooping baskets for plastic tubs
- Climate class 5 for high performance in warm surroundings

Static scoop ice cream freezer

The NIC-SC-SO ice cream freezer offers a stylish design at an affordable price. It has a rounded top trim, curved corners and a curved glass top for a nice product presentation, while sliding lids keep the energy consumption to a minimum when not serving.

The scoop freezer is equipped with LED lighting in the front, making sure your ice cream flavors are always nicely illuminated. The NIC-SC-SO comes with strong castors for mobility.

Be aware that the freezer comes with standard baskets, but if you need baskets suitable for 5 l scoop ice cream tubs, these are available as options. Type and number must be ordered under accessories. These baskets are suitable for 5 l plastic tubs - Napoli pans will not fit in there.

Ideal baskets for scoop ice

- For 5L plastic tubs: 1x item no. 14705 + 1x 14707 (7x 5L)
- For 4L plastic tubs: 5x item no. 21286 (10x 4L)

Measures and Content

Serving Capacity	7 Plastic Tubs (5L) / 10 Plastic Tubs (4L)	
Storage Capacity (under)	13 Plastic Tubs (5L) / 13 Plastic Tubs (4L)	
Temperature Range	°C	-24 to -14
Climate Class	5	
Gross / Net Weight	kg	70.1 / 62.1

Design and Material

Tempered glass	Yes	
Castors	4 wheels, 2 with brake	
Interior Light	LED	
Lock	Yes	
Exterior Finish	White	
Interior Finish	White painted steel	

Cooling and Functions


Type of Controller	Mechanical	
Type of Cooling	Static	
Type of Defrost	Manual	
Refrigerant	R290	
Refrigerant Charge	g	85
Thermometer	Yes	

Power and Consumption

Energy Class	D	
Max Ambient	+40°C, 40% RH	
Annual Energy Cons.	kWh/year	592.76
Energy Consumption	kWh/24h	1.624
EEL	%	41.8
Input Power	W	200
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	45

Dimensions

External Dimension (WxDxH)	mm	1030 x 650 x 885
Packed Dimension (WxDxH)	mm	1100 x 765 x 940
40ft Container Load	pcs	64



Scooping basket option



Castors with and without brake