



NIC502SC-SO

Scoop Ice Cream Freezer

Product Features

- Sneeze guard in curved glass
- Flat sliding glass lids with lock
- Great branding possibilities
- LED interior light
- Castors with brake
- Digital thermometer
- Powder coated white steel inner liner
- Optional - Scooping baskets for plastic tubs
- Climate class 5 for high performance in warm surroundings

Static scoop ice cream freezer

The NIC-SC-SO ice cream freezer offers a stylish design at an affordable price. It has a rounded top trim, curved corners and a curved glass top for a nice product presentation, while sliding lids keep the energy consumption to a minimum when not serving. The scoop freezer is equipped with LED lighting in the front, making sure your ice cream flavors are always nicely illuminated. The NIC-SC-SO comes with strong castors for mobility.

Be aware that the freezer comes with standard baskets, but if you need baskets suitable for 5 l scoop ice cream tubs, these are available as options. Type and number must be ordered under accessories. These baskets are suitable for 5 l plastic tubs - Napoli pans will not fit in there.

Ideal baskets for scoop ice

- For 5L plastic tubs: 3x item no.14707 (12x 5L)
- For 4L plastic tubs: 8x item no. 21286 (16x 4L)

Measures and Content

Serving Capacity	11 Plastic Tub (5L) / 16 Plastic Tub (4L)	
Storage Capacity (under)	22 Plastic Tub (5L) / 22 Plastic Tub (4L)	
Temperature Range	°C	-24 to -14
Climate Class	5	
Gross / Net Weight	kg	122.1 / 110.1

Design and Material

Tempered glass	Yes	
Castors	4 wheels, 2 with brake	
Interior Light	LED	
Lock	Yes	
Exterior Finish	White	
Interior Finish	White painted steel	

Cooling and Functions

Type of Controller	Mechanical	
Type of Cooling	Static	
Type of Defrost	Manual	
Refrigerant	R290	
Refrigerant Charge	g	110
Thermometer	Yes	

Power and Consumption

Energy Class	D	
Max Ambient	+40°C, 40% RH	
Annual Energy Cons.	kWh/year	828.55
Energy Consumption	kWh/24h	2.27
EEL	%	43.9
Power Supply	13 Amp	
Input Power	W	265
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	45

Dimensions

External Dimension (WxDxH)	mm	1570 x 650 x 885
Packed Dimension (WxDxH)	mm	1640 x 765 x 940
40ft Container Load	pcs	42



Castors with and without brake