



Galaxy+ GP20FGD Maxi Black

Supermarket Multideck Cooler

Product Features

- EU Energy Class B
- Can be multiplexed - Create uninterrupted continuous line
- Frameless glass doors for great product visibility
- Adjustable shelves with tilting function
- Heavy duty shelving with strengthening bar
- Ticket strip and acrylic front riser as standard
- Self-closing doors
- Solid 40 mm endwalls with mirrored interior
- Stainless steel bumper bars
- Ventilated cooling
- Multiplexing kit as accessory

880 mm deep multideck cooler with doors

With this full glass door multideck cooler, you get a gorgeous design combined with an energy efficient cooling system. The frameless full vision glass doors allow for great visibility of the products inside. Vertical LED lights run down the inside of each wall, which combined with horizontal LED lighting across the top give excellent illumination and make the contents stand out. The shelves can be tilted to optimize product presentation. Multiplexing kits are available as accessories, so you can create uninterrupted lines throughout your store. As a result of a carefully designed refrigeration system and optimal airflow through the cooler, this cabinet has an outstanding low energy consumption and an impressive EU energy rating.

Measures and Content

Total Display Area	m ²	3.1
Temperature Range	°C	-1 to +5
Climate Class		3
Net Volume	l	1208
Gross Volume	l	2598
Gross / Net Volume	l	2598 / 1208
Gross / Net Weight	kg	394 / 372

Design and Material

Door No & Type	4 hinged glass doors	
Tempered glass		Yes
No. of Doors		4
Max load on Shelves	kg/m ²	160
No. of Shelves	pcs	5
Shelf Color		Black
Shelf Dimensions		938x500mm
Shelves No & Type		5 adjustable
Feet / Legs		6 adjustable feet
Interior Light		LED
Exterior Finish		Black RAL9005
Interior Finish		Black RAL9005

Cooling and Functions

Type of Controller		Electronic
Type of Defrost		Automatic
Refrigerant		R290
Refrigerant Charge	g	150
Thermometer		Yes

Power and Consumption

Energy Class		B
Annual Energy Cons.	kWh/year	2066
Energy Consumption	kWh/24h	5.66
EEL	%	12
Input Power	W	259
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	55

Dimensions

External Dimension (WxDxH)	mm	1955 x 880 x 2040
Internal Dimension (WxDxH)	mm	1875 x 684 x 1562
Packed Dimension (WxDxH)	mm	2000 x 930 x 2320
40ft Container Load	pcs	12



Full height doors



Frameless glass doors