TEFCOLD®
COOL PRODUCTS WORLDWIDE



CRPF1815

Cold Room

Product Features
- Plug-In - ready after assembly
- Many customisation possibilities
- Easy access to products
- Easy assembly
- Anti-slip floor in SS304 stainless steel
- 80 mm panel insulation
- Shelves available as accessory
- Ramp available as accessory for easy access

Easy, economic and effective storage in cold rooms

Measures and Content		
Wall Thickness	mm	80
Internal Volume	m³	4.48
Temperature Range	°C	0 to +8
Gross / Net Weight	kg	362 / 332
Design and Material		
Door No & Type		1 hinged solid door W:700 H:1845
No. of Doors		1
Max Load on Floor	kg/m²	1500
Interior Light		LED
Lock		Yes
Exterior Finish		White
Interior Finish		White
Cooling and Functions		
Type of Controller		Electronic
Type of Defrost		Automatic, hot gas
Refrigerant		R290
Refrigerant Charge	g	130
Thermometer		Yes
Power and Consumption		
Annual Energy Cons.	kWh/year	6545
Energy Consumption	kWh/24h	17.93
Power Supply		13 Amp
Input Power	W	830
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	60
Dimensions		
External Dimension (WxDxH)	mm	1800 x 1500 x 2200
Internal Dimension (WxDxH)	mm	1640 x 1340 x 2040
Packed Dimension (WxDxH)	mm	2200 x 1300 x 2400
40ft Container Load	pcs	14

Strong handle

Shelf as accessory

Cold rooms are perfect as plug-in with quick and easy assemble.

The cooling unit comes completely pre-mounted in a panel and does not require extra expert knowledge. The interchangeable modular panels even allow varies positioning of both the panel with the cooling unit and the panel with the door.

The cold room can be used in both restaurants, delis, cafes etc. They are a great way to create optimal and efficient cooling space at a very affordable price. Cold rooms are a perfect and easy accessable way to store foods, dairy products and beverages.

The many different cold room sizes give a good fit in most conditions. Cold rooms are available as both cooler and freezer models. Shelves are optional. A ramp is also available as an option to provide easy access with lightweight trolleys and bakery racks (the cold room is not suitable for pallet jacks/pallet trucks).

Our range of cold rooms have a low energy consumption due to the effective polyurethane insulation in the panels combined with an energy efficient cooling system.

Not suitable for outdoor use.