



GVC33-120

Vitrine Cooler GN1/4

Product Features

- Stainless steel
- Glass structure for protection of food
- Accepts GN1/4 pan(s) (not supplied)
- Digital controller and temperature display
- Static cooling
- Adjustable feet

Refrigerated topping unit for GN1/4 pans

The GVC is designed to meet the demands of fast-paced food service. Whether you're running a pizzeria, fast-food restaurant, or sandwich shop, this vitrine cooler makes food prep easier, ensuring everything you need is organized and within reach. The topping unit accepts gastronorm pans (not included) – see the technical specifications for more information about the capacity of this specific unit.

The GVC maintains optimal temperatures with a reliable static cooling system. This keeps your ingredients fresh and ready to use, while the manual defrost feature prevents ice build-up for hassle-free operation.

Constructed from durable SS201 stainless steel, the topping shelf is built to last and is equipped with a glass sneeze guard. This ensures hygiene by protecting the food and offers excellent visibility for quick access to your toppings. Perfect for businesses where speed and quality are essential, the GVC is designed to optimize your food prep process

Measures and Content

| | | |
|--------------------|-----|-----------|
| Capacity GN Pans | pcs | 5 x GN1/4 |
| Temperature Range | °C | +2 to +8 |
| Net Volume | l | 26 |
| Gross Volume | l | 31 |
| Gross / Net Volume | l | 31 / 26 |
| Gross / Net Weight | kg | 29 / 25 |

Design and Material

| | |
|-----------------|-----------------|
| Tempered glass | Yes |
| Feet / Legs | Adjustable feet |
| Exterior Finish | SS201 |
| Interior Finish | SS201 |

Cooling and Functions

| | | |
|--------------------|------------|----|
| Type of Controller | Electronic | |
| Type of Cooling | Static | |
| Type of Defrost | Manual | |
| Refrigerant | R600a | |
| Refrigerant Charge | g | 45 |
| Thermometer | Yes | |

Power and Consumption


| | | |
|---------------------|---------------|------------|
| Max Ambient | +30°C, 55% RH | |
| Annual Energy Cons. | kWh/year | 964 |
| Energy Consumption | kWh/24h | 2.64 |
| Power Supply | 13 Amp | |
| Input Power | W | 110 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Noise Level | dB(A) | 40 |

Dimensions

| | | |
|----------------------------|-----|------------------|
| External Dimension (WxDxH) | mm | 1200 x 335 x 448 |
| Internal Dimension (WxDxH) | mm | 850 x 245 x 150 |
| Packed Dimension (WxDxH) | mm | 1300 x 375 x 280 |
| 40ft Container Load | pcs | 324 |



Glass structure for protection of food



Accepts GN1/4 pan(s) (not supplied)