



SGD-240GE

High-end Backbar Cooler

Product Features

- Excellent product visibility
- Suitable for bottles and KEGS
- Low energy consumption
- Adjustable plate shelves
- LED interior light with switch
- Skinplate exterior/interior
- Digital controller and temperature display
- Adjustable legs
- Automatic defrost
- Easy maintenance condenser
- Lock

Spacious backbar cooler with glass doors

The SGD glass door version is built to deliver exceptional style and product presentation combined with superior energy efficiency. This premium cabinet works well for displaying cans and bottles of different shapes and sizes, as the adjustable plate shelves provide a stable, practical surface for easy organization.

Designed with hospitality in mind, the SGD features a sleek anthracite exterior that blends effortlessly into modern, high-end settings. Its coated skinplate interior and exterior are resistant to scratches and visible fingerprints, ensuring it stays looking great even with daily use.

The energy-efficient cooling system ensures a consistent temperature while keeping running costs under control. The temperature is easy to set on the electronic controller and it has automatic defrost for easy maintenance.

Measures and Content

Temperature Range	°C	+2 to +10
Climate Class - DELETE		4
Gross / Net Weight	kg	118 / 105
Gross Volume	l	282
Net Volume	l	260
Gross / Net Volume	l	282 / 260

Design and Material

Bottom Shelf Dimensions		1042 x 220
Door No & Type		2 hinged glass doors
Max load on Shelves	kg/m²	165
No. of Doors		2
No. of Shelves	pcs	4
Shelf Color		Silver
Shelf Dimensions		510 x 355 mm
Shelves No & Type		4 adjustable
Tempered glass		No
Feet / Legs		Adjustable feet
Exterior Finish		Anthracite RAL 7021
Interior Finish		Silver
Interior Light		LED
Lock		Yes

Cooling and Functions

Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic
Refrigerant		R290
Refrigerant Charge	g	85
Thermometer		Yes

Power and Consumption


Energy Class		F
Energy Consumption	kWh/24h	7.06
Annual Energy Cons.	kWh/year	2577
EEl	%	67.1
Input Power	W	280
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	47

Dimensions

Internal Dimension (WxDxH)	mm	1040 x 425 x 682
External Dimension (WxDxH)	mm	1110 x 620 x 840
Packed Dimension (WxDxH)	mm	1145 x 640 x 965 mm
40ft Container Load	pcs	76



Adjustable shelves



Digital controller